

## WITH GAL- Xe ONE-TECHNOLOGY

## **GUARANTEED ANALYSIS:**

TOTAL NITROGEN (N)*	
TOTAL NITROGEN (N)* 7.40% Ammoniacal Nitrogen	
6.00% Nitrate Nitrogen	
5.60% Urea Nitrogen	
AVAILABLE PHOSPHĂTE (P <sub>2</sub> O <sub>5</sub> )*	6.00%
SOLUBLE POTASH (K <sub>2</sub> O)*	
Magnesium (Mg)	
Sulfur (S)*	4 70%
Copper (Cu)	0.05%
Iron (Fe)	1.50%
Iron (Fe)	.0.05%
Molvbdenum (Mo)	
Zinc (Zn)	0.05%

Derived from Polymer-Coated Sulfur-Coated Urea, Polymer-Coated Ammonium Nitrate, Polymer-Coated Ammonium Phosphate, Polymer-Coated Calcium Phosphate, Polymer-Coated Ammonium Polyphosphate, Polymer-Coated Sulfate of Potash, Magnesium Carbonate, Magnesium Oxide, Magnesium Sulfate, Copper Oxide, Copper Sulfate, Ferric Oxide, Ferrous Sulfate, Manganese Oxide, Manganese Sulfate, Sodium Molybdate, Zinc Oxide and Zinc Sulfate.

\*A portion of the nitrogen, phosphate, potash and sulfur materials in this product have been coated to provide 19.00% coated slow release nitrogen (N), 6.00% coated slow release available phosphate (P<sub>2</sub>O<sub>5</sub>), 10.00% coated slow release soluble potash (K<sub>2</sub>O), and 3.50% coated slow release sulfur (S).



## WITH GAL- X ONE -TECHNOLOGY

	5	
U.S. STANDARD		ELEMENTAL
	GUARANTEED ANALYSIS:	
	TOTAL NITROGEN (N)**	
	7.40% Ammoniacal Nitrogen	
	6.00% Nitrate Nitrogen	
	5.60% Urea Nitrogen	
6.00%	AVAILABLE PHOSPHATE (P <sub>2</sub> O <sub>5</sub> )**	2 60%
	SOLUBLE POTASH (K <sub>2</sub> O)**	8 30%
0.50%	Magnesium (Mg)	0.50%
	Magnesium (Mg) Sulfur (S)**	4 70%
	Copper (Cu) Iron (Fe) Manganese (Mn)	0.05%
0.05% 1.50%	Iron (Fe)	1 50%
0.05%	Manganese (Mn)	
0.0005%	Molybdenum (Mo)	0.0005%
0.05%	Zinc (Zn)	0.05%
um Nitrate, Polymer-Coated	Derived from Polymer-Coated Sulfur-Coated Urea, Polymer-Coated	ed Ammonium Nitrate, Polymer-Coated

Coated Calcium Phosphate, Polymer-Coated Ammonium Polymer-Coated Sulfate of Potash, Magnesium Carbonate, Magnesium Oxide, Magnesium Sulfate, Copper Oxide, Copper Sulfate, Ferric Oxide, Ferrous Sulfate, Magnesie Oxide, Magnesie Sulfate, Sodium Molybdate, Zinc Oxide and Zinc Sulfate.

\*\*A portion of the nitrogen, phosphorus, potassium and sulfur materials in this product have been coated to provide 19.00% coated slow release nitrogen (N), 2.60% coated slow release total phosphorus (P), 8.30% coated slow release total potassium (K), and 3.50% coated slow release sulfur (S).

4 to 5

MONTH

DESCRIPTION: UP TO 4 TO 5 MONTH & PROFESSIONAL CONTROLLED RELEASE NURSERY FERTILIZER FOR SHORT TERM CROPS SUCH AS ANNUALS AND PERENNIALS. PROVIDES THE MAJORITY OF THE PRIMARY, SECONDARY AND MICRO ELEMENTS THAT ARE ESSENTIAL FOR HEALTHY PLANT GROWTH.

KEEP OUT OF REACH OF CHILDREN WARNING

! CAUSES SKIN IRRITATION. CAUSES EYE IRRITATION. MAY CAUSE RESPIRATORY IRRITATION.

PRECAUTONARY STATEMENTS: Avoid preating dust. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Call a poison center / doctor if you feel unwell. Specific treatment see First Aid section on this label. PERSONAL PROTECTIVE EQUIPMENT: Wear protective gloves / protective clothing / eye protection / face protection. Take off contaminated clothing and wash before reuse. FIRST AID: IF ON SKIN Wash with plenty of water. If skin irritation occurs get medical advice / attention. STORAGE AND DISPOSAL: STORAGE Store in a well-ventilated place. Keep container tightly closed. Store locked up. DISPOSAL Dispose of contents / container in accordance with all applicable federal, state, and local regulations.

			• •							•		
<ul> <li>BENEFITS:</li> <li>Release of nutrients with GAL-Xe<sup>ONE</sup> is predictable and reliable. The coating has been precisely applied to ensure the effectiveness of each granule.</li> <li>Release of nutrients is not significantly affected by media type, moisture level, pH, or microbial activity.</li> </ul>								SOIL / MEDIA TEMPERATURE RELEASE RATES 50°F 10.0°C = 7.8 month 60°F 15.5°C = 6.7 month 70°F 21.0°C = 4.5 month ◊ 80°F 26.5°C = 3.4 month				
APPLICATION RATES: (Call for rates on larger containers.) Use LOW rate for low feeding, sensitive plants or under high soil temperatures. Use MEDIUM rate for medium to moderately heavy feeding plants. Use HIGH rate only for heavy feeding hardy plants.						ON TABLE	11 11 11 11	Level Measure 1 teaspoon (tsp.) 1 tablespoon (tblsp.) 1/4 cup 1/2 cup		6.2 18.4 61.4 124.0		Oz (Wt.) 0.22 0.65 2.17 4.37
These application rates are based on the average temperature at the fertilizer location of 70°F (21.0°C). Increase fertilizer application rates by 20% if average monthly temperatures are lower than 60°F (15.5°C). Lower application rates by 20% if average monthly temperatures are greater than 80°F (26.5°C).					CONVERSION	APEX SPOONS	ze Grams 11.0 17.0 22.2 27.4	Oz.(Wt.) 0.39 0.60 0.78 0.97	5 6 7 8	Grams 38.5 54.8 71.9 87.2	<b>Oz.(Wt.)</b> 1.36 1.93 2.54 3.08	
TOPDRESS CONTA VOLUME (gal.) 1 gallon 2 gallons 3 gallons 5 gallons 7 gallons 10 gallons 15 gallons	AINER: Plant Nutrient Re DIAMETER 6 inches 8 inches 10 inches 12 inches 14 inches 17 inches 18 inches	equirements / Uniform LOW 3 g 6 g 12 g 18 g 26 g 45 g 60 g	nly apply (topdress MEDIUM 6 g 12 g 24 g 36 g 52 g 90 g 120 g	s) product onto the HIGH 9 g 18 g 36 g 54 g 78 g 135 g 180 g	e container surface using the amounts listed b DIAMETER (mm) 100 mm 125 mm 150 mm 175 mm 200 mm 250 mm 300 mm	elow. LO\ 0.6 1.2 2.0 3.5 5.0 12.0 16.0	g g g g g g g g g g g g g g g g g g g	Ν		HIGH 1.8 g 3.6 g 6.0 g 10.5 g 15.0 g 36.0 g 48.0 g		
INCORPORATION: Pla POUNDS PER CUBIC YAI		Uniformly mix (incor MED 6	, ,		media as follows: KILOGRAMS PER CUBIC METRES	LC	DW 1.	8 M	ED 3.6		HIGH	5.4
PLANTING BED: FIEL POUNDS PER 100 SQ. FE				,	WS: KILOGRAMS PER 100 SQ. METRES	LC	DW 7	М	ED 15		HIGH	22
Application precautions:     Trial before use of this product under your local growing conditions, application methods, and desired rates.     Avoid application to plants under stress.     If mixed media is not used within one week, leach thoroughly before using.     Product left in media for more than one week will lose longevity resulting in reduced release time and wasted controlled release fertilizer.     Avoid the use of media processing equipment that could change the integrity of the polymer coating.     Avoid mounding of fertilizer against base of plant.     Iron and other plant nutrients can cause staining of cament.				<ul> <li>Keep away from pools, ponds, and other bodies of water.</li> <li>When using potting media with higher cation exchange capacities use lower recommended rates of this formulation.</li> <li>When using supplemental liquid feed reduce the rate of this formulation accordingly.</li> <li>Do not incorporate into media prior to steam sterilization.</li> <li>This product is not recommended for dibble applications.</li> <li>To avoid buildup of soluble salts, occasional leaching may be necessary.</li> <li>CAUTION: Application of fertilizer materials containing Molybdenum (Mo) may result in forage crops containing levels of Molybdenum (Mo) that are toxic to ruminant animals.</li> </ul>								

Warning: This product contains a chemical known to the State of California to cause cancer, birth defects or other reproductive harm. Proposition 65, the Safe Drinking Water and Toxic Enforcement Act of 1986, requires

notification of potential exposure to substances identified by the State of California as causing cancer, birth defects or other reproductive harm. Information regarding the contents and levels of metals in this product is available on the internet at http://www.regulatory-info-jr.com

DISCLAIMER OF WARRANTIES: Seller warrants that the composition of this product conforms to the description given on this label. THIS WARRANTI IS EXPRESSLY IN LIEU OF ALL OTHER WARRANTIES AND REPRESENTATIONS EXPRESSED, IMPLIED, OR STATUTORY, INCLUDING WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR USE. Timing, rate and method of application, weather and crop conditions, mixtures not specifically recommended on this label or an accompanying written recommendation, are beyond the control of the seller. Buyer assumes all risks of use, storage and handling of this material not in strict accordance with directions given herewith. Buyer further agrees in the event of damages ansing from the use of this product to accept a replacement of the product or a refundes of the product or a sfull discharge of seller's liability. No one is authorized to make any other warranty, guarantee or directions concerning this product, and no such warranties, guarantees or directions shall be valid or binding upon seller.


## U.S. STANDARD - NET WEIGHT 50 LB. (22.68 KG.)





APEX® is a registered trademark of the J.R. Simplot Company. GAL-Xe<sup>ONE</sup> is a trademark of J.R. Simplot Company. For more enquiries on these products, please email us now. info@centaur-asiapacific.com

Website: www.centaur-asiapacific.com



ITEM#75329 DUAL GHS R3-20-2015

ELEMENTAL - NET WEIGHT 22.68 KG.